

Delivery Inspection Report

commodity	Compressor heater		specifications	220V50W570*1200
Production quantity			production date	
Inspection quantity			Inspection plan	according to GB5013.3-2008 nominal inspect plan II standard
The serial number	Conclusion test items and technical requirements		test results	conclusion
1	appearance: red silica gel, the surface has no obvious scar, without impurities and air bubbles, no mechanical damage, lead no distortions.		Red silica gel, the surface has no obvious scar, without impurities and air bubbles, no mechanical damage, lead no distortions.	
2	size (mm)	length: 410mm±5mm	405mm—415mm	
		width: 14mm±0.5mm	13.5mm—14.5mm	
		lead: 1200mm±10mm	1190mm—1210mm	
3	power: 50w±7%		46.5W--53.5W	
4	Insulation resistance	should be greater than 4, 100 m Ω (DC500V, flooding)	More than 100MΩ	
5	electric strength	AC2000V / 2 S no breakdown flashover phenomenon (immersed)	AC2000V / 2 S no breakdown flashover phenomenon)	
6	mechanical strength	Between lead and heating element sealing is good, should be able to withstand 50 N / 60 S not deformation, no crack phenomenon	withstand 50 N/ 60 S not deformation, no crack phenomenon	
		The hang after riveting should be able to withstand 80 N, not fall off after 10S.	Don't fall off after withstand 80 N / 10S	
		Terminal and wire connection should be able to withstand 50 N, not fall off after 10 S.	Don't fall off after withstand 50 N / 10 S	
7	leakage current should be less than 0.1 mA (immersed)		is less than 0.1 mA	
conclusion	This batch of products			