

VACUUM PUMP

V. Technical Parameter

		Vakum Pompasi													
Model		CL110		CL115		CL125		CL135		CL160		CL180		CL1100	
Voltage		220V	110V	220V	110V	220V	110V	220V	110V	220V	110V	220V	110V	220V	110V
		50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz
Free Air Displacement	m3/saat	1.8	2	1.8	2	3	3.5	5	6	8	9	10	11.8	12	13.8
	Lt/saat	30	34	30	34	50	58	84	100	140	170	198	226	230	254
Ultimate Vacuum	Pa	5		5		5		5		5		5		5	
	mbar	0.05		0.05		0.05		0.05		0.05		0.05		0.05	
	microns														
Motor		1/5Hp		1/4Hp		1/4Hp		1/3Hp		1/2Hp		3/4Hp		1Hp	
Intake Fitting		1/4"		1/4"		1/4"		1/4"		1/4" & 3/8"		1/4" & 3/8"		1/4" & 3/8"	
Oil Capacity		200		320		250		280		450		800		950	
Dimensions (mm)		255x105x205		270x120x225		270x120x225		275x120x235		320x135x250		370x148x265		390x148x265	
Net Weight(kg)		4.2		5.2		6.8		8.5		9.8		14.2		14.5	

VACUUM PUMP

		Vakum Pompasi													
Model		CL215		CL225		CL235		CL245		CL260		CL280		CL2100	
Voltage		220V	110V	220V	110V	220V	110V	220V	110V	220V	110V	220V	110V	220V	110V
		50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz
Free Air Displacement	m3/saat	1.5	1.8	3.2	4	4.5	5.2	5.5	6.5	8	9	10.5	12.6	13	14.8
	Lt/saat	25	30	53	67	70	84	128	142	170	198	226	254	280	340
Ultimate Vacuum	Pa	0.3		0.3		0.3		0.3		0.3		0.3		0.3	
	mbar	0.003		0.003		0.003		0.003		0.003		0.003		0.003	
	microns	25		25		25		25		25		25		25	
Motor		1/4Hp		1/3Hp		1/3Hp		1/2Hp		3/4Hp		1Hp		1Hp	
Intake Fitting		1/4"		1/4"		1/4"		1/4" & 3/8"		1/4" & 3/8"		1/4" & 3/8"		1/4" & 3/8"	
Oil Capacity		180		270		300		360		650		650		750	
Dimensions (mm)		270x120x225		275x120x250		320x135x250		320x135x250		370x148x265		370x148x265		390x148x265	
Net Weight(kg)		6.0		6.5		8.8		11.5		14.8		15.3		16	